

HYPHONE

INTRODUCTION

www.hyphone.com.tw

2" (3") Mini Sander Powerful & Easy Handling



HY-1382A



HY-1382C



HY-1382E



HY-1382F

Specification	HY-1382A	HY-1382C	HY-1382E	HY-1382F
Application	Mini Sanding/Stripping/Polishing Sander			
Power (hp)	0.35			
Pad size	2" or 3" (Velcro)		2" or 3" (Roloc)	
Orbit	3 mm	none	none	none
Trigger Style	Lever		Lever	Knob
Spindle	5/16" - 24 UNF		1/4"-20	
Free speed (rpm)	16,000	19,000	19,000	
Exhaust	Side swivel collar			
Sound pressure / power	81 / 92 dBA	80 / 91 dBA	80 / 91 dBA	
Weight	1.32 lb / 0.6 Kg	1.0 lb / 0.45 Kg	1.0 lb / 0.45 Kg	
Height (with Pad)	4.65" / 118 mm	3.78" / 96 mm	4.09" / 104 mm	3.54" / 90 mm
Air consumption @ 90psi	3.1 cfm / 88 L/min			
Air inlet in.	1/4"			
Minimum hose size	3/8" (10mm)			

Hyphone Machine Industry

TEL:886-4-2563-3678

21, Lane 742, Sec 1, He-Mu Rd. Shen Gang Dist.

Taichung, Taiwan